

# LED T8 4-FT Tube

Damp Rated, Up to 135 lm/W, G13, Type B, Double Ended Power

## FEATURES

<b>Lumen Output</b>	1800 to 2250 lumens
<b>Efficacy</b>	Up to 135 lm/W
<b>Input Voltage</b>	120-277V
<b>Driver</b>	Type B (Internal Driver)
<b>Installation</b>	Double Ended Power
<b>Dimmable</b>	No
<b>Size</b>	4-FT
<b>CCT</b>	4000K, 5000K
<b>Rating</b>	Damp Location
<b>Warranty</b>	5 Years

## APPLICATIONS

Premium indoor replacement lamp intended to replace 4 foot T8 or T12 fluorescent lamps with G13 end caps for linear lamp fixtures. Suitable for use in linear troffers, wraparounds, and shop lights.

## CONSTRUCTION

Manufactured for durability and heat dissipation using aluminum sheet backing. Damp Location rated.

## ELECTRICAL

Input voltage 120-277V. Type B, to operate without a ballast. Double Ended Power installations for G13 end caps. Operating temperatures -4°F to 113°F (-20°C to 45°C).

## MOUNTING

Replacement lamp twist-locks into existing linear T8 lamp fixture.

## OPTICS

Shatter resistant anti-UV Frosted Polycarbonate Lens with 325° beam angle.

## CONTROLS

Compatible with ON/OFF occupancy sensors.

## LISTINGS

DLC listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

## WARRANTY

5 year exclusive limited warranty.

## LAMP

SMARTSOURCE LED

Project:
Date:
Catalog No:
Prepared By:



4-FT Models



## CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



## SPECIFICATIONS

## ENERGY DATA

**Input Voltage:** 120-277V**Input Frequency:** 50/60 Hz**Wattage:** 14.5W, 17W**Power Factor:** >0.9**Total Harmonic Distortion (THD):** <20%**Operating Temperature:** -4°F to 113°F (-20°C to 45°C)

## LIGHTING DATA

**Lumens:** 1800 to 2250**Lumens Per Watt:** Up to 135 lm/W**Correlated Color Temperature (CCT):** 4000K, 5000K**Dimmable:** No**Color Rendering Index (CRI):** 80**L70:** 50000 hours

## ORDERING INFORMATION

Model	Size	Type	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color
SSL-48T8-840-14P-G8R-DW	4-FT	G13	14.5W	120-277V	0.13A@120V, 0.06A@277V	1800	130 lm/W	4000K	No	White
SSL-48T8-850-14P-G8R-DW	4-FT	G13	14.5W	120-277V	0.13A@120V, 0.06A@277V	1800	130 lm/W	5000K	No	White
SSL-48T8-840-17P-G8R-DW	4-FT	G13	17W	120-277V	0.16A@120V, 0.07A@277V	2250	135 lm/W	4000K	No	White
SSL-48T8-850-17P-G8R-DW	4-FT	G13	17W	120-277V	0.16A@120V, 0.07A@277V	2250	135 lm/W	5000K	No	White

