

LED Linear High Bay

3-Wattages + 3-CCT (35/40/50K), Damp Rated, 150 lm/W, Dimmable + Smart



SMARTSOURCE LED

LUMINAIRE

Project:
Date:
Catalog No:
Prepared By:

FEATURES

Lumen Output	24750 to 48000 lumens
Efficacy	150 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	4-FT
CCT	Select (3500K, 4000K, 5000K)
Rating	Damp Location
Warranty	7 Years

APPLICATIONS

Premium indoor luminaire for hanging or pendant mounting in high ceiling spaces above 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, and covered decks.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Ventilated driver bay for additional heat dissipation. Damp Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 104°F (-20°C to 40°C).

MOUNTING

Aluminum V-Hooks and Chains for hanging standard. Optional Pendant Mount Bracket or pair of 10-FT Aircraft Hanging Cables available.

OPTICS

Anti-UV Frosted Polycarbonate Lens standard. Protective Wire Guards available.

CONTROLS

Installed fixture mounted Occupancy Sensor (On/Off), or Smart Sensor for Photocell with Bi-Level Motion Dimmer and Remote Control available. Installed Step-Down Autotransformer for 480V to 277V applications available.

EMERGENCY

Installed 90 Minute Emergency Backup Battery Driver options available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

7 year exclusive limited warranty.

4-FT Models



Proprietary Flat Standard Design



Occupancy Sensor



Smart Sensor



Emergency Driver



Remote Control





TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 3-Wattages (220W Max, 320W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <15%
Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: 24750 to 48000
Lumens Per Watt: 150 lm/W
Correlated Color Temperature (CCT): 3-CCT (35K, 40K, 50K)
Dimmable: 0-10V
Color Rendering Index (CRI): >80
L70: 75000 hours

ORDERING INFORMATION


Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-B04-220-185-165W-3CCT	4-FT	(165W, 185W, 220W)	120-277V	1.51A@120V, 0.66A@277V 1.70A@120V, 0.73A@277V 2.02A@120V, 0.87A@277V	24750 27750 33000	150 lm/W	(3500K, 4000K, 5000K)	0-10V	White	45.75"L x 12.63"W x 2.13"H
SSL-B04-320-300-240W-3CCT	4-FT	(240W, 300W, 320W)	120-277V	2.20A@120V, 0.95A@277V 2.75A@120V, 1.19A@277V 2.93A@120V, 1.27A@277V	36000 45000 48000	150 lm/W	(3500K, 4000K, 5000K)	0-10V	White	45.75"L x 17.76"W x 3.00"H

Housing	Mount	Control	Emergency
B0-WG4-M Wire Guard (Fits: 4-FT 220W Max models)	B0-PM-M Pendant Mount (Fits: 4-FT 220W Max models)	BRI819P-B-O [INSTALLED] PIR Sensor with On/Off Occupancy	EM15 [INSTALLED] Emergency LED Driver, 15W, 90-Min Battery
B0-WG4-L Wire Guard (Fits: 4-FT 320W Max models)	B0-PM-L Pendant Mount (Fits: 4-FT 320W Max models)	BRI819P-B-D [INSTALLED] PIR Sensor with Daylight Priority	EM25 [INSTALLED] Emergency LED Driver, 25W, 90-Min Battery
	B0-SMK Surface Mount Kit	RC-100 Remote Control for Sensor Settings	EM40 [INSTALLED] Emergency LED Driver, 40W, 90-Min Battery
	AC-10 Pair of 10-FT Aircraft Hanging Cables	SD250 [INSTALLED] Step-Down Autotransformer 480V to 277V, Up To 250W	
	(Blank) V-Hooks and Chains (Standard)	SD375 [INSTALLED] Step-Down Autotransformer 480V to 277V, Up To 375W	

PHYSICAL DIMENSIONS

220W Max Models

45.75"L x 12.63"W x 2.13"H



320W Max Models

45.75"L x 17.76"W x 3.00"H

