

TriLum Tunable

LED Canopy Light

3-Wattages + 3-CCT (35/40/50K), Wet Rated, 130 lm/W, Dimmable + Smart



LUMINAIRE

SMARTSOURCE LED

Project:
Date:
Catalog No:
Prepared By:

FEATURES

Lumen Output	5200 to 10400 lumens
Efficacy	130 lm/W
Input Voltage	120-277V, or 277-480V
Dimmable	0-10V Continuous
CCT	Select (3500K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

APPLICATIONS

Premium outdoor luminaire for surface mounting in ceiling spaces less than 25 feet. Suitable for general storage, cold storage, parking garages, and canopies.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

ELECTRICAL

Input voltages 120-277V with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattage. Operating temperatures -40°F to 104°F (-40°C to 40°C).

MOUNTING

Surface mounted installation.

OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens.

CONTROLS

Installed fixture mounted PIR or Microwave Sensor with Daylight Priority. Remote Control or Bluetooth App Control options available.

EMERGENCY

Installed 90 Minute Emergency Backup Battery Driver options available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

Tunable 80W Max Models



PIR Sensor or Bluetooth



Microwave Sensor or Bluetooth



Remote Control



LCD Remote Control



Emergency Driver





TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V, 277-480V

Input Frequency: 50/60 Hz

Wattage: 3-Wattages (80W Max)

Power Factor: >0.9

Total Harmonic Distortion (THD): <10%

Operating Temperature: -4°F to 104°F (-20°C to 40°C)

LIGHTING DATA

Lumens: 5200 to 10400

Lumens Per Watt: 130 lm/W

Correlated Color Temperature (CCT): 3-CCT (35K, 40K, 50K)

Dimmable: 0-10V

Color Rendering Index (CRI): >80

L70: 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-GCP-80/60/40W-H-TCP	(40W 60W 80W)	120-277V	0.44A@120V, 0.16A@277V 0.66A@120V, 0.24A@277V 0.88A@120V, 0.32A@277V	5200 7800 10400	130 lm/W	(3500K, 4000K, 5000K)	0-10V	Bronze	10.06"L x 10.06"W x 2.73"H
Control			Emergency						
HD07VR-MH	Microwave Sensor with Daylight Priority		EM8	[INSTALLED] Emergency LED Driver, 8W, 90-Min Battery					
HD07VR-MHB	Microwave Sensor with Daylight Priority (Bluetooth/App Controlled)		EM20	[INSTALLED] Emergency LED Driver, 20W, 90-Min Battery					
HD07VR-PH	PIR Sensor with Daylight Priority								
HD07VR-PHB	PIR Sensor with Daylight Priority (Bluetooth/App Controlled)								
HD03R	Remote Control for Sensor Settings								
HD05R	Remote Control for Sensor Settings w/ LCD								

PHYSICAL DIMENSIONS

80W Max Model

10.06"L x 10.06"W x 2.73"H

