

LED Slim Wall Pack

3-Wattages + 3-CCT (30/40/50K), Wet Rated, 138 lm/W, Dimmable + Smart



SMARTSOURCE LED

LUMINAIRE

Project:
Date:
Catalog No:
Prepared By:

Tunable 60W Max and 120W Max Models in Bronze or White Housing



FEATURES	
Lumen Output	4140 to 16560 lumens
Efficacy	138 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3000K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

APPLICATIONS

Premium outdoor luminaire suitable for wall mounting on building exteriors for entrances, courtyards, alleys, and pedestrian walkways.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 113°F (-20°C to 45°C).

MOUNTING

Wall mounted installations. Includes Liquid Level inside housing.

OPTICS

Anti-UV Clear Prismatic Tempered Glass Lens.

CONTROLS

Installed fixture integrated Photocell sensor available. Installed fixture integrated PIR Sensor with Daylight Priority available. Remote Control available.

LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

PIR Sensor




Remote Control



TUNABLE CORRELATED COLOR TEMPERATURES (CCT)


3000K



4000K



5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 3-Wattages (60W Max, 120W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <20%
Operating Temperature: -4°F to 113°F (-20°C to 45°C)

LIGHTING DATA

Lumens: 4140 to 16560
Lumens Per Watt: 138 lm/W
Correlated Color Temperature (CCT): 3-CCT (30K, 40K, 50K)
Dimmable: 0-10V
Color Rendering Index (CRI): >80
L70: 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-H-60/40/30W-G5-TCP	(30W, 40W, 60W)	120-277V	0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V 0.55A@120V, 0.24A@277V	4140 5520 8280	138 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	13.74"L x 9.25"W x 4.29"D
SSL-H-120/100/80W-G5-TCP	(80W, 100W, 120W)	120-277V	0.73A@120V, 0.32A@277V 0.92A@120V, 0.40A@277V 1.10A@120V, 0.48A@277V	11040 13800 16560	138 lm/W	(3000K, 4000K, 5000K)	0-10V	Bronze	13.74"L x 9.25"W x 4.29"D
SSL-H-60/40/30W-G5-TCP-WH-PCB	(30W, 40W, 60W)	120-277V	0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V 0.55A@120V, 0.24A@277V	4140 5520 8280	138 lm/W	(3000K, 4000K, 5000K)	0-10V	White	13.74"L x 9.25"W x 4.29"D
SSL-H-120/100/80W-G5-TCP-WH-PCB	(80W, 100W, 120W)	120-277V	0.73A@120V, 0.32A@277V 0.92A@120V, 0.40A@277V 1.10A@120V, 0.48A@277V	11040 13800 16560	138 lm/W	(3000K, 4000K, 5000K)	0-10V	White	13.74"L x 9.25"W x 4.29"D

Control

PCB	[[INSTALLED] Integrated Photocell Sensor
BRI823-X-D	[[INSTALLED] Line Voltage PIR Sensor with Daylight Priority
RC-100	Remote Control for Sensor Settings

PHYSICAL DIMENSIONS

All Models

13.74"L x 9.25"W x 4.29"D

