

LED Post Top Lantern

3-Wattages + 3-CCT (30/40/50K), Wet Rated, 105 lm/W, Dimmable

LUMINAIRE

SMARTSOURCE LED

FEATURES	
Lumen Output	3150 to 10500 lumens
Efficacy	105 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
CCT	Select (3000K, 4000K, 5000K)
Rating	Wet Location
Warranty	5 Years

Project:
Date:
Catalog No:
Prepared By:

30W 3-CCT and Tunable 100W Max Models include Photocell Sensor



APPLICATIONS

Premium outdoor luminaire suitable for entrances, building exteriors, parks, and pedestrian walkways.

CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3000K, 4000K, 5000K), Single Wattage, and Tunable 3-Wattage models. Operating temperatures -40°F to 113°F (-40°C to 45°C).

MOUNTING

Includes 3-inch Slip-Fit Pole Mounting base.

OPTICS

Anti-UV Frosted Tempered Glass IES/ NEMA Type 5 Lens.

CONTROLS

Includes NEMA 3-Pin Photocell Sensor Cap.

LISTINGS

DLC listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

Photocell Sensor





TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3000K

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 30W, 3-Wattages (100W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <15%
Operating Temperature: -40°F to 113°F (-40°C to 45°C)

LIGHTING DATA

Lumens: 3150 to 10500
Lumens Per Watt: 105 lm/W
Correlated Color Temperature (CCT): 3-CCT (30K, 40K, 50K)
Dimmable: 0-10V
Color Rendering Index (CRI): >70
L70: 50000 hours

ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-TP350-30W	30W	100-277V	0.28A@120V, 0.12A@277V	3150	105 lm/W	(3000K, 4000K, 5000K)	0-10V	Black	13.80"L x 13.80"W x 24.92"H
SSL-TP350-W100-C3	(30W, 60W, 100W)	100-277V	0.28A@120V, 0.12A@277V 0.55A@120V, 0.24A@277V 0.92A@120V, 0.40A@277V	3150 6300 10500	105 lm/W	(3000K, 4000K, 5000K)	0-10V	Black	13.80"L x 13.80"W x 24.92"H

PHYSICAL DIMENSIONS

All Models

13.80"L x 13.80"W x 24.92"H

