

# LED Spider Post Top Light

Wet Rated, 130 lm/W, Dimmable



## LUMINAIRE

SMARTSOURCE LED

Project:
Date:
Catalog No:
Prepared By:

150W and 300W Models



### CORRELATED COLOR TEMPERATURE (CCT)

5000K



### FEATURES

<b>Lumen Output</b>	19500 to 39000 lumens
<b>Efficacy</b>	130 lm/W
<b>Input Voltage</b>	120-277V
<b>Dimmable</b>	0-10V Continuous
<b>CCT</b>	5000K
<b>Rating</b>	Wet Location
<b>Warranty</b>	5 Years

### APPLICATIONS

Premium outdoor luminaire suitable for entrances, building exteriors, parks, and pedestrian walkways.

### CONSTRUCTION

Manufactured for weather-proof durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, salt, corrosion, discoloration, and scratching. Wet Location rated.

### ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Operating temperatures -40°F to 113°F (-40°C to 45°C).

### MOUNTING

Includes 3-inch Slip-Fit Pole Mounting base.

### OPTICS

Anti-UV Clear Polycarbonate IES/ NEMA Type 5 Lens.

### LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

### WARRANTY

5 year exclusive limited warranty.

## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V  
**Input Frequency:** 50/60 Hz  
**Wattage:** 150W, 300W  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** <15%  
**Operating Temperature:** -40°F to 113°F (-40°C to 45°C)

### LIGHTING DATA

**Lumens:** 19500 to 39000  
**Lumens Per Watt:** 130 lm/W  
**Correlated Color Temperature (CCT):** 5000K  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >70  
**L70:** 50000 hours

## ORDERING INFORMATION

Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-TP500-W150	100W	120-277V	1.38A@120V, 0.60A@277V	19500	130 lm/W	5000K	0-10V	Black	20.75"L x 15.84"W x 21.72"H
SSL-TP500-W300-NP-Y6	150W	120-277V	2.75A@120V, 1.19A@277V	39000	130 lm/W	5000K	0-10V	Black	20.75"L x 15.84"W x 21.72"H

## PHYSICAL DIMENSIONS

### All Models

20.75"L x 15.84"W x 21.72"H

