

TriLum Tunable

# LED Slim Round High Bay

3-Wattages + 3-CCT (35/40/50K), Wet Rated, 140 lm/W, Dimmable + Smart



SMARTSOURCE LED

## LUMINAIRE

Project:
Date:
Catalog No:
Prepared By:

150W Max and 240W Max Models



### FEATURES

<b>Lumen Output</b>	14000 to 33600 lumens
<b>Efficacy</b>	140 lm/W
<b>Input Voltage</b>	120-277V
<b>Dimmable</b>	0-10V Continuous
<b>CCT</b>	Select (3500K, 4000K, 5000K)
<b>Rating</b>	Wet Location
<b>Warranty</b>	5 Years

### APPLICATIONS

Premium indoor luminaire for hanging or pendant mounting in high ceiling spaces above 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, and covered decks.

### CONSTRUCTION

Manufactured for durability using solid heavy duty die cast aluminum housing with anti-UV polyester coating to resist water, corrosion, discoloration, and scratching. Wet Location rated.

### ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -40°F to 113°F (-40°C to 45°C).

### MOUNTING

Steel Hook Mount for hanging standard. Optional adjustable Yoke Mount for surface mounting available.

### OPTICS

Anti-UV Clear Polycarbonate Ridged Lens with 80 degree beam angle standard. 90 degree Aluminum and Prismatic Polycarbonate Reflectors available. Glare Shield Polycarbonate Drop Lens available.

### CONTROLS

Installed fixture mounted PIR or Microwave Sensor with Daylight Priority. Remote Control or Bluetooth App Control options available. Installed Step-Down Auto-transformer for 480V to 277V applications available.

### EMERGENCY

Installed 90 Minute Emergency Backup Battery Driver available.

### LISTINGS

DLC Premium pending. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

### WARRANTY

5 year exclusive limited warranty.

Hook Mount



Yoke Mount



PIR Sensor or Bluetooth



Microwave Sensor or Bluetooth



Remote Control



LCD Remote Control



Emergency Driver



### TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K



4000K



5000K



## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V  
**Input Frequency:** 50/60 Hz  
**Wattage:** 3-Wattages (150W Max, 240W Max)  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** 10%  
**Operating Temperature:** -40°F to 113°F (-40°C to 45°C)

### LIGHTING DATA

**Lumens:** 14000 to 33600  
**Lumens Per Watt:** 140 lm/W  
**Correlated Color Temperature (CCT):** 3-CCT (35K, 40K, 50K)  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >80  
**L70:** 50000 hours

## ORDERING INFORMATION


Model	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-TUFO-150/120/100W-H-TCP(XX)-Y	(100W, 120W, 150W)	120-277V	0.92A@120V, 0.40A@277V 1.10A@120V, 0.48A@277V 1.38A@120V, 0.60A@277V	14000 16800 21000	140 lm/W	(3500K, 4000K, 5000K)	0-10V	Black	ø11.02"C x 5.73"H
SSL-TUFO-240/200/150W-H-TCP(XX)-Y	(150W, 200W, 240W)	120-277V	1.38A@120V, 0.60A@277V 1.83A@120V, 0.79A@277V 2.20A@120V, 0.95A@277V	21000 28000 33600	140 lm/W	(3500K, 4000K, 5000K)	0-10V	Black	ø13.31"C x 5.81"H

Optics	Control	Emergency
TTLUFO-REF-AL-L Aluminum Reflector 90 Degrees (Fits: 240W Max model)	HD07VR-MH Microwave Sensor with Daylight Priority	EMB30R [INSTALLED] Emergency LED Driver, 30W, 90-Min Battery
TTLUFO-REF-PR-L Prismatic Polycarbonate Reflector 90 Degrees (Fits: 240W Max model)	HD07VR-MHB Microwave Sensor with Daylight Priority (Bluetooth/App Controlled)	
TTLUFO-GLS Glare Shield Polycarbonate Drop Lens (Fits: 240W Max model)	HD07VR-PH PIR Sensor with Daylight Priority	
TTLUFO-Y-S Yoke Mount (Fits: 150W Max model)	HD07VR-PHB PIR Sensor with Daylight Priority (Bluetooth/App Controlled)	
TTLUFO-Y-L Yoke Mount (Fits: 240W Max model)	HD03R Remote Control for Sensor Settings HD05R Remote Control for Sensor Settings w/ LCD	

## PHYSICAL DIMENSIONS

### 150W Max Models

ø11.02"C x 5.73"H



### 240W Max Models

ø13.31"C x 5.81"H

