



# LED Vapor Tight

3-Wattages + 3-CCT (35/40/50K), Wet Rated, 135 lm/W, Dimmable + Smart

## FEATURES

<b>Lumen Output</b>	8775 to 12150 lumens
<b>Efficacy</b>	135 lm/W
<b>Input Voltage</b>	120-277V
<b>Dimmable</b>	1-10V Continuous
<b>Size</b>	4-FT, 8-FT
<b>CCT</b>	Select (3500K, 4000K, 5000K)
<b>Rating</b>	Wet Location
<b>Warranty</b>	5 Years

## APPLICATIONS

Premium indoor luminaire for hanging or surface mounting in ceiling spaces less than 25 feet. Suitable for gymnasiums, warehouses, manufacturing, packaging, storage, aisles, work-stations, and covered decks.

## CONSTRUCTION

Manufactured for durability with injection molded polycarbonate to resist corrosion, discoloration, and scratching. Stainless steel clips lock the lens cover to resist dust, moisture and vapors. Wet Location rated.

## ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Tunable 3-CCT (3500K, 4000K, 5000K) and Tunable 3-Wattages. Operating temperatures -4°F to 104°F (-20°C to 40°C).

## MOUNTING

Aluminum Surface Mount Clips standard.

## OPTICS

Anti-UV Frosted Polycarbonate Lens standard.

## CONTROLS

Installed fixture integrated PIR Sensor with Daylight Priority available. Remote Control available.

## EMERGENCY

Installed 90 Minute Emergency Backup Battery LED Driver available.

## LISTINGS

DLC Premium listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

## WARRANTY

5 year exclusive limited warranty.

## LUMINAIRE

SMARTSOURCE LED

Project:
Date:
Catalog No:
Prepared By:

Tunable 8-FT Model



PIR Sensor



Remote Control



Emergency Driver






## TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K

4000K

5000K



## SPECIFICATIONS

### ENERGY DATA

**Input Voltage:** 120-277V  
**Input Frequency:** 50/60 Hz  
**Wattage:** 3-Wattages (90W Max)  
**Power Factor:** >0.9  
**Total Harmonic Distortion (THD):** <15%  
**Operating Temperature:** -4°F to 104°F (-20°C to 40°C)

### LIGHTING DATA

**Lumens:** 8775 to 12150  
**Lumens Per Watt:** 135 lm/W  
**Correlated Color Temperature (CCT):** 3-CCT (35K, 40K, 50K)  
**Dimmable:** 0-10V  
**Color Rendering Index (CRI):** >80  
**L70:** 75000 hours

## ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-VP8FT657590W27	8-FT	(65W 75W 90W)	120-277V	0.60A@120V, 0.26A@277V 0.69A@120V, 0.30A@277V 0.83A@120V, 0.36A@277V	8775 10125 12150	135 lm/W	(3500K, 4000K, 5000K)	1-10V	Gray	94.50"L x 5.00"W x 3.50"H
Control				Emergency						
<b>BRI823-X-D</b>	[[INSTALLED] Line Voltage PIR Sensor with Daylight Priority			<b>EM6</b>	INSTALLED - Emergency LED Driver, 6W, 90-Minute Battery					
<b>RC-100</b>	Remote Control for Sensor Settings									

## PHYSICAL DIMENSIONS

### 8-FT Models

94.50"L x 5.00"W x 3.50"H

