

DuraGem

LED Wraparound

Damp Rated, 130 lm/W, Dimmable



LUMINAIRE

SMARTSOURCE LED

Project:
Date:
Catalog No:
Prepared By:

FEATURES

Lumen Output	2860 to 5200 lumens
Efficacy	130 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	4-FT
CCT	4000K, 5000K
Rating	Damp Location
Warranty	7 Years

APPLICATIONS

Premium indoor luminaire suitable for general indoors, lobbies, offices, meeting rooms, restrooms, hallways, stairwells, storage-closets, kitchens, and work-stations.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Damp Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Operating temperatures -4°F to 122°F (-20°C to 50°C).

MOUNTING

Surface Mounting on ceilings or beams.

OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens standard.

LISTINGS

DLC listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

7 year exclusive limited warranty.

4-FT Models



CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V

Input Frequency: 50/60 Hz

Wattage: 22W, 40W

Power Factor: >0.9

Total Harmonic Distortion (THD): <10%

Operating Temperature: -4°F to 122°F (-20°C to 50°C)

LIGHTING DATA

Lumens: 2860 to 5200

Lumens Per Watt: 130 lm/W

Correlated Color Temperature (CCT): 4000K, 5000K

Dimmable: 0-10V

Color Rendering Index (CRI): >82

L70: 75000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
SSL-WRP-4-22W-4K	4-FT	22W	120-277V	0.18A@120V, 0.08A@277V	2860	130 lm/W	4000K	0-10V	White	47.75"L x 7.12"W x 2.80"H
SSL-WRP-4-22W-5K	4-FT	22W	120-277V	0.18A@120V, 0.08A@277V	2860	130 lm/W	5000K	0-10V	White	47.75"L x 7.12"W x 2.80"H
SSL-WRP-4-40W-4K	4-FT	40W	120-277V	0.33A@120V, 0.14A@277V	5200	130 lm/W	4000K	0-10V	White	47.75"L x 7.12"W x 2.80"H
SSL-WRP-4-40W-5K	4-FT	40W	120-277V	0.33A@120V, 0.14A@277V	5200	130 lm/W	5000K	0-10V	White	47.75"L x 7.12"W x 2.80"H

PHYSICAL DIMENSIONS

4-FT Model

47.75"L x 7.12"W x 2.80"H

